

Viti testa esagonale parzialmente filettate



ISO 4014

d	M 5	M 6	M 8	M 10	M 12	M 14	M 16	M 18
l / mm								
25		●						
30	●	●	●					
35	●	●	●	●				
40	●	●	●	●	●			
45	●	●	●	●	●			
50	●	●	●	●	●	●	●	
55	●	●	●	●	●	●	●	
60	●	●	●	●	●	●	●	
65	●	●	●	●	●	●	●	●
70	●	●	●	●	●	●	●	●
75		●	●	●	●	●	●	●
80	●	●	●	●	●	●	●	●
85		●	●	●	●	●	●	
90	●	●	●	●	●	●	●	●
100	●	●	●	●	●	●	●	●
110		●	●	●	●	●	●	●
120		●	●	●	●	●	●	●
130		●	●	●	●	●	●	●
140		●	●	●	●	●	●	●
150		●	●	●	●	●	●	●
160		●	●	●	●	●	●	●
170		●	●	●	●	●	●	●
180		●	●	●	●	●	●	●
190			●	●	●	●	●	
200			●	●	●	●	●	●
210			●	●	●		●	
220			●	●	●		●	
230				●	●		●	
240			●	●	●		●	
250				●	●		●	
260				●	●		●	
270							●	
280				●	●		●	
290							●	
300				●	●		●	
320				●	●		●	
340				●	●		●	

Viti testa esagonale parzialmente filettate



ISO 4014

d	M 5	M 6	M 8	M 10	M 12	M 14	M 16	M 18
l / mm								
360				●	●		●	
380				●	●		●	
400				●	●		●	
420				●	●		●	
440				●	●		●	
460				●	●		●	
480				●	●		●	
500				●	●		●	
CONFEZIONE	200 ≤ 70	200 ≤ 45	100 ≤ 70	100 ≤ 50	50 ≤ 75	50 ≤ 110	25 ≤ 160	25
	100 >70	100 >45	50 ≤ 160	50 ≤ 160	25 ≤ 160	25 ≤ 160	10 >160	
			25 >160	25 ≤ 210	10 >160	10 >160		
				10 >210				
b per l -125mm	16	18	22	26	30	34	38	42
b per 125 mm < l -200mm	–	–	–	–	–	40	44	48
b per l > 200mm	–	–	–	–	–	–	–	–
k	3,5	4	5,3	6,4	7,5	8,8	10	11,5
e	8,79	11,05	14,38	17,77	20,03	24,49	26,75	30,14
s	8	10	13	16	18	22	24	27
* ISO 4014=SW cambiato M 10, M 12, M 14, M 22								

Viti testa esagonale parzialmente filettate



ISO 4014

d	M 20	M 22	M 24	M 27	M 30	M 33	M 36
l / mm							
60	●						
65	●						
70	●						
75	●						
80	●	●	●	●	●		
85	●		●				
90	●	●	●	●	●	●	
95	●		●				
100	●	●	●	●	●	●	●
110	●	●	●	●	●	●	●
120	●	●	●	●	●	●	●
130	●	●	●	●	●	●	●
140	●	●	●	●	●	●	●
150	●	●	●	●	●	●	●
160	●	●	●	●	●	●	●
170	●		●	●	●	●	●
180	●	●	●	●	●	●	●
190	●		●	●	●	●	●
200	●	●	●	●	●	●	●
210	●		●	●	●	●	●
220	●		●	●	●	●	●
230	●		●	●	●	●	●
240	●		●	●	●	●	●
250	●		●	●	●	●	●
260	●		●				
270	●		●				
280	●		●				
290	●		●				
300	●		●				
320	●		●				
340	●		●				
360	●		●				
380	●		●				
400	●		●				
420	●		●				
440	●		●				
460	●		●				

Viti testa esagonale parzialmente filettate



ISO 4014

d	M 20	M 22	M 24	M 27	M 30	M 33	M 36
l / mm							
480	●		●				
500	●		●				
520	●		●				
540	●		●				
560	●		●				
580	●		●				
600	●		●				
CONFEZIONE	25	25 ≤ 110	10 ≤ 210	10 ≤ 160	10 ≤ 160	10 ≤ 130	10 ≤ 130
		20 ≤ 160	5 > 210	5 > 160	5 > 160	5 > 130	5 > 130
		10 > 160					
<i>b per l - 125mm</i>	46	50	54	60	66	72	78
<i>b per 125 mm < l - 200mm</i>	52	56	60	66	72	78	84
<i>b per l > 200mm</i>	-	69	73	79	85	91	97
<i>k</i>	12,5	14	15	17	18,7	21	22,5
<i>e</i>	33,53	35,72	39,98	45,2	50,85	55,37	60,79
<i>s</i>	30	32	36	41	46	50	55
* ISO 4014=SW cambiato M 10, M 12, M 14, M 22							