

Viti di sicurezza / A2

Viti atf. testa svasata piana TX + piolino



d	3,5 No. 6	4,2 No. 8	4,8 No. 10	5,5 No. 12	6,3 No. 14
l / mm (pollice)					
13 (1/2")	1 3 3 5 4 7	1 3 3 6 4 7	1 3 3 7 5 2	1 3 3 8 2 7	
16 (5/8")	1 3 3 5 5 2	1 3 3 6 5 2	1 3 3 7 5 7	1 3 3 8 3 2	1 3 3 9 0 7
19 (3/4")	1 3 3 5 5 7	1 3 3 6 5 7	1 3 3 7 6 2	1 3 3 8 3 7	1 3 3 9 1 2
25 (1")	1 3 3 5 6 2	1 3 3 6 6 2	1 3 3 7 6 7	1 3 3 8 4 2	1 3 3 9 1 7
32 (1 1/4")	1 3 3 5 6 7	1 3 3 6 8 0	1 3 3 7 7 5	1 3 3 8 4 7	1 3 3 9 2 2
38 (1 1/2")	1 3 3 5 7 2	1 3 3 6 9 2	1 3 3 7 8 2	1 3 3 8 5 2	1 3 3 9 2 7
50 (2")			1 3 3 7 8 7	1 3 3 8 5 4	1 3 3 9 3 2
63 (2 1/2")				1 3 3 8 6 2	
75 (3")				1 3 3 8 7 0	
<i>Ø testa</i>	7,8	9,1	10,5	11,1	13,5
<i>altezza testa</i>	3,3	3,8	4,3	4,4	5,1
<i>unità</i>	TX15	TX20	TX25	TX30	TX30
<i>articolo bit</i>	1 3 9 8 0 5	1 3 9 8 1 0	1 3 9 8 1 5	1 3 9 8 2 5	1 3 9 8 2 5
confezione	100	100	100	100	100