

**DIN 912 / A4**

**Viti testa cilindrica con esagono incassato**




ISO 4762

d	M 1,6	M 2	M 2,5	M 3	M 4	M 5	M 6	M 8	M 10	M 12
l / mm										
3	●	●								
4	●	●	●	●						
5	●	●	●	●	●					
6	●	●	●	●	●	●	●			
8	●	●	●	●	●	●	●			
10		●	●	●	●	●	●	●		
12		●	●	●	●	●	●	●	●	
14		●	●	●	●	●	●	●		
16		●	●	●	●	●	●	●	●	●
18		●	●	●	●	●	●	●	●	
20		●	●	●	●	●	●	●	●	●
22				●	●	●	●	●		
25				●	●	●	●	●	●	●
30				●	●	●	●	●	●	●
35				●	●	●	●	●	●	●
40				●	●	●	●	●	●	●
40/40							●			
45				●	●	●	●	●	●	●
50				●	●	●	●	●	●	●
55						●	●	●	●	●
60					●	●	●	●	●	●
65							●	●	●	●
70					●	●	●	●	●	●
75							●	●	●	●
80						●	●	●	●	●
85						●				
90						●	●	●	●	●
100						●	●	●	●	●
110						●	●	●	●	●
120						●	●	●	●	●
130							●	●	●	●
140							●	●	●	●
150							●	●	●	●
160							●	●	●	●
170							●	●	●	●
180							●	●	●	●
200							●	●	●	●

**DIN 912 / A4**

**Viti testa cilindrica con esagono incassato**



ISO 4762

d	M 1,6	M 2	M 2,5	M 3	M 4	M 5	M 6	M 8	M 10	M 12
l / mm										
210								●	●	●
220							●	●	●	●
230								●	●	●
240								●	●	●
250								●	●	●
260								●	●	●
270										●
280								●	●	●
300								●	●	●
CONFEZIONE	500	500	500	1000	1000	500	500	500	100	50
				≤ 35	≤ 20	≤ 25	≤ 14	≤ 14	≤ 50	≤ 75
				500	500	200	200	200	50	25
				≤ 50	≤ 35	≤ 80	≤ 45	≤ 25	≤ 170	
				200	200	100	100	100	25	
				>50	≤ 60	>80	>45	≤ 100	>170	
b	15	16	17	18	20	22	24	28	32	36
t min	0,7	1	1	1	2	3	3	4	5	6
s	1,5	1,5	2	2,5	3	4	5	6	8	10
k max	1,6	2	2,5	3	4	5	6	8	10	12
dk	3	3,8	5	5,5	7	9	10	13	16	18

**DIN 912 / A4**

**Viti testa cilindrica con esagono incassato**



d	M 14	M 16	M 18	M 20	M 24	M 27	M 30
l / mm							
20	●	●					
25	●	●					
30	●	●		●			
35	●	●		●			
40	●	●	●	●	●		
45	●	●	●	●	●		
50	●	●	●	●	●	●	●
55	●	●	●	●	●		
60	●	●	●	●	●	●	●
65	●	●	●	●	●		
70	●	●	●	●	●	●	●
75	●	●	●	●	●		
80	●	●	●	●	●	●	●
90	●	●	●	●	●	●	●
100	●	●	●	●	●	●	●
110	●	●	●	●	●	●	●
120	●	●	●	●	●	●	●
130	●	●	●	●	●	●	●
140	●	●	●	●	●	●	●
150	●	●	●	●	●	●	●
160		●		●	●		
170		●		●	●		
180		●		●	●		
190		●		●	●		
200		●		●	●		

**DIN 912 / A4**

**Viti testa cilindrica con esagono incassato**



d	M 14	M 16	M 18	M 20	M 24	M 27	M 30
l / mm							
CONFEZIONE	50 ≤ 110	25	25	25	10	10	10
	25 >110						
b	40	44	48	52	60	66	72
t min	7	8	9	10	12	13,5	15,5
s	12	14	14	17	19	19	22
k max	14	16	18	20	24	27	30
dk	21	24	27	30	36	40	45