

Viti testa esagonale parzialmente filettate



ISO 4014

d	M 5	M 6	M 8	M 10	M 12	M 16	M 20	M 24
l / mm								
30	●	●						
35	●	●	●					
40	●	●	●	●				
45	●	●	●	●	●			
50	●	●	●	●	●			
55	●	●	●	●	●	●		
60	●	●	●	●	●	●		
65		●	●	●	●	●	●	
70	●	●	●	●	●	●	●	
75		●	●	●	●	●	●	
80	●	●	●	●	●	●	●	●
85								●
90	●	●	●	●	●	●	●	●
100	●	●	●	●	●	●	●	●
110		●	●	●	●	●	●	●
120		●	●	●	●	●	●	●
130		●	●	●	●	●	●	●
140		●	●	●	●	●	●	
150		●	●	●	●	●		
160			●	●	●			
170				●	●			
180			●	●	●			
190				●	●			
200			●	●	●			
210				●	●			
220			●	●	●			

Viti testa esagonale parzialmente filettate



ISO 4014

d	M 5	M 6	M 8	M 10	M 12	M 16	M 20	M 24
l / mm								
CONFEZIONE	200 ≤ 70	200 ≤ 45	100 ≤ 70	100 ≤ 50	50 ≤ 75	25	25	25
	100 >70	100 >45	50 ≤ 160	50 ≤ 160	25 ≤ 160			
			25 >160	25 ≤ 210	10 >160			
				10 >210				
b per l - 125 mm	16	18	22	26	30	38	46	54
b per 125 mm < l - 200 mm	-	-	-	-	-	44	52	60
b per l > 200 mm	-	-	-	-	-	-	-	73
k	3,5	4	5,3	6,4	7,5	10	12,5	15
e	8,79	11,05	14,38	17,77	20,03	26,75	33,53	39,98
s	8	10	13	16	18	24	30	36
* ISO 4014=SW cambiato M 10, M 12, M 14, M 22								